

SETRON, measuring device, 7KM PAC2200, LCD, L-L: 400 V, L-N: 230 V, 65 A, strd rail instr., 3-phase, Modbus TCP, apparent /active/reactive energy, self-powered, screw terminals



Model		
product brand name	SETRON	
product quality / calibrated	No	
type of measured value detection / load profile	No	
type of signal	S0	
design of the energy counter	Solid-state	
design of the pulse output	Electrical	
Supply voltage		
operating voltage		
<ul style="list-style-type: none"> between L and L / minimum between L and L / maximum between N and L / minimum between N and L / maximum 	3 V 480 V 3 V 276 V	
Protection class		
protection class IP	IP40	
Current		
tariff version of the energy counter	two tariff	
short-term overload current	65 A	
Main circuit		
operating frequency / rated value		
<ul style="list-style-type: none"> minimum maximum 	45 Hz 65 Hz	
operational current / rated value	65 A	
Suitability		
suitability for use	Import/export	
Product function		
product function		
<ul style="list-style-type: none"> backstop blocking code 	Yes Yes	
Display and operation		
display version	digital	
Number		
number of characters that can be displayed	12	
Mechanical Design		
number of modular width units	6	
net weight	528 g	
General Product Approval	Declaration of Conformity	other



UK Declaration of
Conformity

Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=7KM2200-2EA40-1EA1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7KM2200-2EA40-1EA1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=7KM2200-2EA40-1EA1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



