



expansion module I(N),I(Diff),analog N conductor measurement, residual current measurement, 2 analog inputs, plug-in, for 7KM PAC3200 / 4200

Model				
product brand name	SETRON			
product designation	I(N),I(Diff) expansion module, analog N conductor measurement, differential current measurement, 2 analog inputs			
type of voltage supply	via PAC 3200 / PAC4200			
General technical data				
galvanic isolation	Maximum insulation voltage: 500V AC			
degree of pollution	2 according to IEC 61131			
Protection class				
protection class IP	IP20			
combustibility class acc. to UL 94	V 0			
suitability for use	No			
<ul style="list-style-type: none"> reactive power meter 	No			
Connections				
type of electrical connection	screw-type terminals			
Mechanical Design				
height	63 mm			
width	43 mm			
depth	34 mm			
fastening method	pluggable			
Environmental conditions				
ambient temperature / during operation				
<ul style="list-style-type: none"> minimum maximum 	-10 °C 55 °C			
ambient temperature / during storage				
<ul style="list-style-type: none"> minimum maximum 	-25 °C 70 °C			
General Product Approval		EMC	Declaration of Conformity	other

[KC](#)



[UK Declaration of Conformity](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=7KM9200-0AD00-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7KM9200-0AD00-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KM9200-0AD00-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



