



expansion module PROFIBUS DP plug-in, for 7KM PAC3200 / 3220 4200 / 3VA COM100 / 800

Model			
product brand name	SETRON		
product designation	PROFIBUS DP expansion module		
type of voltage supply	via PAC 3200 / PAC4200 / COM100 / 800		
General technical data			
MTBF	141.1 y		
galvanic isolation	Maximum insulation voltage: 500V AC		
reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	P		
degree of pollution	2 according to IEC 61131		
Protection class			
protection class IP	IP20		
combustibility class acc. to UL 94	V 0		
suitability for use	No		
• reactive power meter			
Connections			
type of electrical connection	9-pole Sub-D plug according to IEC 61158		
Mechanical Design			
height	63 mm		
width	43 mm		
depth	22 mm		
fastening method	pluggable		
Environmental conditions			
ambient temperature / during operation			
• minimum	-5 °C		
• maximum	55 °C		
ambient temperature / during storage			
• minimum	-25 °C		
• maximum	70 °C		
Certificates			
reference code / acc. to DIN EN 61346-2	P		
<b>General Product Approval</b>	<b>EMC</b>	<b>Declaration of Conformity</b>	<b>other</b>

[KC](#)



[UK Declaration of Conformity](#)



[Miscellaneous](#)

EG-Konf.



Profibus

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KM9300-0AB01-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7KM9300-0AB01-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7KM9300-0AB01-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KM9300-0AB01-0AA0)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



